

990347

09/741,631
Patent

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1 (previously presented): A method comprising:
determining a code phase of each among a plurality of received signals, wherein said received signals are GPS signals; and
transmitting a time difference between the code phases of at least one pair among the plurality of received signals.

2 (canceled)

3 (originally filed): The method according to claim 1, wherein each among the plurality of received signals has a corresponding periodic code, and
wherein each among the code phases relates to a predetermined position within the corresponding periodic code.

4 (originally filed): The method according to claim 1, wherein each among the plurality of received signals is based at least in part on a corresponding direct-sequence spread spectrum modulated signal.

5 (originally filed): The method according to claim 1, wherein each among the plurality of received signals is based at least in part on a corresponding direct-sequence pseudonoise modulated signal.

6 (originally filed): The method according to claim 1, the method further comprising receiving a composite signal,
wherein each among the plurality of received signals is based at least in part on at least a portion of the composite signal.

990347

09/741,631
Patent

7 (originally filed): The method according to claim 6,

wherein the determining a code phase of each among a plurality of received signals comprises calculating a correlation, for each among the plurality of received signals, between a corresponding code sequence and a signal based at least in part on the composite signal,

wherein each among the plurality of received signals has a corresponding periodic code, and

wherein each among the code phases relates to a corresponding predetermined position within the corresponding periodic code, and

wherein the code sequence relates at least in part to the corresponding periodic code.

8 (previously presented): A method comprising:

determining a code phase of a first received signal; and

determining a code phase of a second received signal,

wherein said first and second received signals are GPS signals, and

wherein the determining a code phase of the second received signal is based at least in part on a time difference between the code phase of the first received signal and the code phase of the second received signal.

9 (canceled)

10 (originally presented): The method according to claim 8, wherein the first received signal has a corresponding periodic code and the second received signal has a corresponding periodic code, and

wherein each among the code phase of the first received signal and the code phase of the second received signal relates to a corresponding predetermined position within the corresponding periodic code.

11 (originally presented): The method according to claim 8, wherein each among the first received signal and the second received signal is based at least in part on a corresponding direct-sequence spread spectrum modulated signal.

12 (originally presented): The method according to claim 8, wherein each among the first received signal and the second received signal is based at least in part on a corresponding direct-sequence pseudonoise modulated signal.

990347

09/741,631
Patent

13 (originally presented): The method according to claim 8, the method further comprising receiving a composite signal, wherein each among the first received signal and the second received signal is based at least in part on at least a portion of the composite signal.

14 (originally presented): The method according to claim 13,

wherein the determining a code phase of a first received signal comprises calculating a correlation between a code sequence and a signal based at least in part on the composite signal,

wherein the first received signal has a corresponding periodic code and the second received signal has a corresponding periodic code, and

wherein each among the code phase of the first received signal and the code phase of the second received signal relates to a corresponding predetermined position within the corresponding periodic code, and

wherein the code sequence relates at least in part to the periodic code corresponding to the first received signal.

15 (previously presented): An apparatus comprising:

a GPS receiver configured to receive a plurality of signals;

a correlator configured to determine a code phase for each among the plurality of received signals; and

a transmitter configured to transmit a time difference between the code phases of at least one pair among the plurality of received signals.

16 (canceled)

17 (originally filed): The apparatus according to claim 15, wherein each among the plurality of received signals has a corresponding periodic code, and

wherein each among the code phases relates to a predetermined position within the corresponding periodic code.

990347

09/741,631
Patent

18 (originally filed): The apparatus according to claim 15, wherein each among the plurality of received signals is based at least in part on a corresponding direct-sequence spread spectrum modulated signal.

19 (originally filed): The apparatus according to claim 15, wherein each among the plurality of received signals is based at least in part on a corresponding direct-sequence pseudonoise modulated signal.

20 (originally filed): The apparatus according to claim 15,

wherein the correlator is further configured to determine a code phase for each among the plurality of received signals at least in part by calculating a correlation, for each among the plurality of received signals, between a corresponding code sequence and the plurality of received signals,

wherein each among the plurality of received signals has a corresponding periodic code;

wherein each among the code phases relates to a corresponding predetermined position within the corresponding periodic code, and

wherein the corresponding code sequence relates at least in part to the corresponding periodic code.

21 (previously presented): An apparatus comprising:

a GPS receiver configured to receive a first and second signal and to receive a signal comprising a time difference between the code phase of the first received signal and the code phase of the second received signal, and

a correlator configured to determine a code phase of at least one of the first and second received signals with respect to a predetermined code and to correlate the other of the first and second received signals to the predetermined code based upon the time relationship between the first and second received signals.

22 (canceled)

990347

09/741,631
Patent

23 (originally filed): The apparatus according to claim 21, wherein the correlator is further configured to determine a code phase for the second received signal at least in part from the information.

24 (previously presented): A system comprising:

a reference receiver configured to receive GPS signals from a plurality of space vehicles and to transmit information; and

a field receiver configured to receive signals from a plurality of space vehicles and to receive the information,

wherein the reference receiver determines a reference code phase for each among at least a first one and a second one of the signals, and

wherein the information pertains at least to a time difference between the reference code phases for the first one and the second one of the signals, and

wherein the field receiver determines a field code phase for the first one of the signals, and

wherein the field receiver determines a field code phase for the second one of the signals at least in part from the information.

25 (canceled)

B1
concl